

YS16WPD10-4-8-S

16-Way Wilkinson Power Divider, 10 W, 4-8 GHz, SMA

Key Features


- 4-8 GHz Wideband Coverage
- Low Insertion Loss
- Excellent Amplitude & Phase Balance
- High Isolation (≥ 18 dB)
- 10 W Power Handling

Applications

- RF & Microwave Systems
- Test & Measurement
- Radar & EW Systems
- Communication Networks
- Signal Distribution

Electrical Specifications		
1	Frequency Range	4-8 GHz
2	Insertion Loss	≤ 2.0 dB
3	Input Port VSWR	$\leq 1.5:1$
4	Output Port VSWR	$\leq 1.3:1$
5	Isolation	≥ 15 dB
6	Amplitude Balance	$\leq \pm 0.4$ dB
7	Phase Balance	$\leq \pm 6^\circ$
8	Power Handling	10 W(CW)
9	Impedance	50 Ω
Environmental Specifications		
1	Operating Temperature	-55°C to +85°C
Mechanical Specifications		
1	Connectors	SMA Female
2	Surface Finishing	Cavity: Silver plated
3	Dimensions ¹	210×64×12 mm / [8.27×2.52×0.47 in]

Outline Drawing (Units: mm/[inch], Tolerance: ± 0.3 mm)



Note 1: Excluding Connectors