

YS2WPD50-R1-R4-S

2-Way Wilkinson Power Divider, 50W, 0.1-0.4 GHz, SMA

Key Features


- 0.1-0.4 GHz Wideband Coverage
- Low Insertion Loss
- Excellent Amplitude & Phase Balance
- High Isolation (≥ 17 dB)
- 50 W Power Handling

Applications

- RF & Microwave Systems
- Test & Measurement
- Radar & EW Systems
- Communication Networks
- Signal Distribution

Electrical Specifications		
1	Frequency Range	0.1-0.4 GHz
2	Insertion Loss	≤ 0.9 dB
3	Input Port VSWR	$\leq 1.4:1$
4	Output Port VSWR	$\leq 1.4:1$
5	Isolation	≥ 17 dB
6	Amplitude Balance	$\leq \pm 0.6$ dB
7	Phase Balance	$\leq \pm 9^\circ$
8	Power Handling	50 W(CW)
9	Impedance	50 Ω
Environmental Specifications		
1	Operating Temperature	-55°C to +85°C
Mechanical Specifications		
1	Connectors	SMA Female
2	Surface Finishing	Natural Conductive Oxidation
3	Dimensions ¹	115×110×11 mm / [4.53×4.33×0.43 in]

Outline Drawing (Units: mm/[inch], Tolerance: ± 0.3 mm)



Note 1: Excluding Connectors