

YS4HPC300-1-6-N

4-Way Hybrid Power Combiner, 300 W, 1-6 GHz, N-Type

Key Features


- Low insertion loss
- High port isolation
- Wide operating bandwidth
- Excellent amplitude and phase balance
- Custom frequency and power options

Applications

- RF power amplifier combining
- Wireless infrastructure
- SATCOM systems
- Radar transmitters
- RF test systems

Electrical Specifications		
1	Frequency Range	1-6 GHz
2	Insertion Loss	≤ 0.7 dB (avg.) / 1.3 dB (max.)
3	Output Port VSWR	$\leq 1.60:1$
4	Isolation	≥ 14 dB
5	Amplitude Balance	$\leq \pm 0.9$ dB
6	Phase Balance	$\leq \pm 10^\circ$
7	Power Handling	300 W(CW)
8	Impedance	50 Ω
Environmental Specifications		
1	Operating Temperature	-55°C to +85°C
Mechanical Specifications		
1	Connectors	N-Type Female, SMA Female
2	Surface Finishing	Natural Conductive Oxidation
3	Dimensions ¹	280×95×31 mm / [11.02×3.74×1.22 in]

Outline Drawing (Units: mm/[inch], Tolerance: ± 0.2 mm)



Note 1: Excluding Connectors