

YS8WPD250-R4-1-S

8-Way Wilkinson Power Divider, 250 W, 0.4-1 GHz, SMA

Key Features


- 0.4-1 GHz Wideband Coverage
- Low Insertion Loss
- Excellent Amplitude & Phase Balance
- High Isolation (≥ 18 dB)
- 250 W Power Handling

Applications

- RF & Microwave Systems
- Test & Measurement
- Radar & EW Systems
- Communication Networks
- Signal Distribution

Electrical Specifications		
1	Frequency Range	0.4-1 GHz
2	Insertion Loss	≤ 0.77 dB
3	Input Port VSWR	$\leq 1.5:1$
4	Output Port VSWR	$\leq 1.4:1$
5	Isolation	≥ 18 dB
6	Amplitude Balance	$\leq \pm 0.2$ dB
7	Phase Balance	$\leq \pm 5^\circ$
8	Power Handling	250 W
9	Impedance	50 Ω
Environmental Specifications		
1	Operating Temperature	-55°C to +85°C
Mechanical Specifications		
1	Connectors	SMA Female
2	Surface Finishing	Cavity: Silver plated Cover: Natural conductive oxidation
3	Dimensions ¹	190×160×15 mm / [7.48×6.30×0.59 in]

Outline Drawing (Units: mm/[inch], Tolerance: ± 0.3 mm)



Note 1: Excluding Connectors