

YSDDC1K-80M-1-50-N

Dual Directional Coupler, 1000 W, 0.08-1 GHz, 50 dB coupling, N-Type

Key Features


- Broadband 0.08-1 GHz operation
- High coupling accuracy: 50 dB \pm 1.0 dB
- Low insertion loss: \leq 0.3 dB
- High power handling: 1000 W (CW)
- Connector type: N-Type Female

Applications

- RF power amplifier monitoring
- VSWR reflected power measurement
- Test & measurement setups
- Microwave system integration
- Lab & production testing

Electrical Specifications		
1	Frequency Range	0.08-1 GHz
2	Coupling	50 \pm 1.0 dB
3	Insertion Loss	\leq 0.3 dB
4	Main Line VSWR	\leq 1.3:1
5	Directivity	\geq 20 dB
6	Power	\leq 1000 W
Environmental Specifications		
1	Operating Temperature	-55°C to +85°C
Mechanical Specifications		
1	Connectors	N-Type Female / SMA Female
2	Surface Finishing	Natural Conductive Oxidation
3	Dimensions ¹	105×54×26 mm / [4.13×2.13×1.02 in]

Outline Drawing (Units: mm/[inch], Tolerance: \pm 0.3 mm)



Note 1: Excluding Connector size