

YSLA25-10M-67-5

Low Noise Amplifier | LNA | 0.01-67 GHz | 25 dB Gain | 5.0 dB NF

Key Features


- Ultra-Wideband Coverage
- High gain low-noise amplifier
- Low Noise Figure
- Compact & Rugged Design

Applications

- RF receiver front-end
- Microwave communication systems
- Radar systems
- Satellite communication
- RF test and measurement

Electrical Specifications				
Parameter	Min.	Typ.	Max.	Unit
Frequency Range	0.01	-	67	GHz
Gain	-	25	-	dB
Gain Flatness	-	±3.0	-	dB
Input VSWR	-	2.0	-	-
Output VSWR	-	2.0	-	-
Output P1dB	-	15	-	dBm
Output Psat	-	16	-	dBm
Spurious	-	-60	-	dBc
OIP3	-	23	-	dBm
Noise Figure	-	5.0	-	dB
Input Max Power(no damage)	-	-	-5	dBm
Supply Voltage	-	+12	-	V
Supply Current	-	300	-	mA
Impedance	50			Ω
Environmental Specifications				
Operating Temperature	-25°C to +85°C			
Storage Temperature	-55°C to +125°C			
* Heat Sink required during operation				
Mechanical Specifications				
Connectors	1.85 mm Female			
Material	Aluminium/Gold Plated			
Weight	50 g			
Dimensions ¹	35×40×12 mm [1.38×1.57×0.47 in]			

Outline Drawing (Units: mm/[inch], Tolerance: ±0.2 mm)



Note 1: Excluding Connectors