

YSPA32-18-26R5-K

18-26.5 GHz Power Amplifier, 32 dB Psat, 2.92 mm

Key Features


- Broadband 18-26.5 GHz coverage
- 32 dBm Psat
- Low spurious emissions
- High reliability for continuous operation
- Compact module with +12 V supply

Applications

- Broadband communication systems
- Radar transmitter subsystems
- RF test and measurement
- Electronic warfare (EW)
- Microwave research laboratories

Electrical Specifications				
Parameter	Min.	Typ.	Max.	Unit
Frequency Range	18	-	26.5	GHz
Gain	18	21	-	dB
Gain Flatness	-	±2.0	±2.5	dB
Input VSWR	-	2.0	2.5	-
Output VSWR	-	2.0	2.2	-
Output P1dB	30	31	-	dBm
Output Psat	-	32	-	dBm
Spurious	-	-60	-	dBc
Input Max Power(no damage)	-	-	15	dBm
Supply Voltage	-	+12	-	V
Supply Current	-	0.5	1.2	A
Impedance	50			Ω
Environmental Specifications				
Operating Temperature	-25°C to +85°C			
Storage Temperature	-55°C to +125°C			
* Heat Sink required during operation				
Mechanical Specifications				
Connectors	2.92 mm Female			
Material	Aluminium / Gold Plating			
Weight	25 g			
Dimensions ¹	25.4×50×8 mm [1.00×1.97×0.31 in]			

Outline Drawing (Units: mm/[inch], Tolerance: ±0.2 mm)



Note 1: Excluding Connectors