

YSRT30-18-N

Coaxial RF Termination, DC-18 GHz, 30 W, N-Type Connector, 50 Ohm

Key Features

- 30 W avg. power @ 25°C
- DC to 18 GHz frequency range
- VSWR ≤ 1.40
- N-Type male connector options


Applications

- Test & measurement systems
- Microwave & RF laboratory setups
- High-frequency communication systems
- Radar and aerospace electronics
- Component characterization and calibration

Electrical Specifications					
1	Nominal Impedance	50 Ω			
2	Average Power ¹	30 W @ 25°C			
3	Frequency Range	DC-4 GHz	DC-8 GHz	DC-12.4 GHz	DC-18 GHz
4	VSWR	≤ 1.20	≤ 1.25	≤ 1.35	≤ 1.40
Environmental Specifications					
1	Operating Temperature	-55°C to +125°C			
Mechanical Specifications					
1	Connectors	N-Type Male			
2	Body Material	Connector: Copper-Based Ternary Alloy Plating Heat Sink: Black Anodized Aluminum			

Note 1: Refer to the power derating curve for details.

Outline Drawing (Units: mm/[inch], Tolerance: ±0.3 mm)



Outline A

Ordering Information:

Model	Connector Type	Outline Drawing
YSRT30-18-N	N-Type Female (default)	
YSRT30-18-NM	N-Type Male	Outline A

Model: **YSRT30-XX-N**

XX = Frequency Range (4 GHz, 8 GHz, 12.4 GHz, 18 GHz)

Example: 8 GHz → **YSRT30-8-N**